

Housing $\phi 16 \times L25\text{mm}$ DC Brushless Motor B1625M

OUTPUT : 0.1W~2W (APPROX)

Bearing TYPE : スリーブ / Sleeve Bushing

WEIGHT(APPROX) : 18g

代表的用途 / Typical Application

家電機器 / 白物家電、調理家電、ファン、理美容家電 / 事務機器 / プリンタ、スキャナ、プロジェクト、医療・計測機器 / ポンプ、血圧計、攪拌器、分離器 /

Household App / Home Electric App, Electric Cooker, Fan, Shaver, Hair Curler

Office Automation Equipment / Printer, Scanner, Projector

Medical App / Medical Pump, Blood Pressure Meter, Medical Stirrer/ DIY App / Electric Pump, Screw Driver


Characteristic : CW/CCW, PWG speed control, Locked rotor protection,

IC Heat protection, Life expectancy 10,000-30,000hrs,

Motor Parameter


No.	Standard Model No.	Product No.	Outline Size			Rated Voltage (V)	No Load		at Max Efficiency					at Stall			Configuration
			Motor OD (mm)	Housing Length (mm)	Shaft OD (mm)		No Load Speed (rpm)	No Load Current (A)	Rated Speed (rpm)	Rated Current (A)	Rated Torque (mN-m, g·cm)		Output (W)	Starting Torque (mN-m, g·cm)		Starting Current (A)	
1	B1625M	-S01	16	25	1.5	12	8790	0.02	6440	0.07	0.7	7.0	0.46	2.56	26.1	0.19	bushing
2		-S02	16	25	1.5	9	8780	0.03	6540	0.09	0.7	7.0	0.47	2.69	27.4	0.27	bushing
3		-S03	16	25	1.5	6	8460	0.04	6450	0.13	0.7	7.0	0.46	2.87	29.3	0.41	bushing

OUTLINE & Inner Driver I/O




Typical Performance

B1625M-S01 (12V)



B1625M-S03 (6V)



Japan Magnets.,Inc

Head Office / Japan Bldg 4F, 1-1646-2, Kamikawa, Suwa, Nagano, Japan zipcode 392-0021

Tel /+81-266-56-1021

Fax /+81-266-56-1430

HP / <http://www.jmi-motion.com>